

Ecoteller Mini ATM



TECHNICAL DATA

Installation Type

- Lobby, Cash Dispenser with front replenishment
- Indoor - Table top/ Wall Mountable

Processor

- Intel 1.6Ghz dual core processor
- Storage: Transaction image, Electronic Journal backup for 6 months

Currency Chest

- Business Hour compliant safe
- Vortex Dual-combination electronic lock

Dispenser

- Gravity assisted Friction pick technology
- Bunch presenter with a maximum capacity of 40 notes per transaction
- 2-cassette configuration
- Cassette capacity - holds 2500 pieces of fresh currency notes
- Convenience cassettes
- Purge bin

Card reader

- Dip card reader
- EMV Version 4.0

Finger Print reader

Customer Interface on ATM

- 10-inch LCD with vandal-proof screen
- 8 FDks
- EPP Keypad - PCI-certified
- Audio jack with speaker for voice guidance
- In-built portrait camera
- Privacy filter

Receipt Printer

- 40-column Graphic Thermal Receipt printer, with a roll paper diameter of 150mm

ATM Security

- PADSS3.2 certified
- Security suite for OS/ Application hardening
- Hardware access protection

HDD

- 500GB

ATM Software

- Linux O/S
- Vortex Swave Terminal Application
- EMV Level 2
- Electronic Journal

Management software

- Vortex Management Center - server application for EJ pulling / remote ATM administration / content download
- Vortex Management Agent

Network Connectivity

- Supports TCP / IP protocol
- Can connect through VSAT, LAN, Leased line, GSM

Operating temperature & Environment protection

- Temperature: 5°C to 45°C
- Humidity: 10% to 90% RH

Power

- Input : 230V AC, 50Hz
- ATM average power consumption - 70W

Weight

- 60kg (with Business Hour compliant safe)

Dimensions

- 435mm (W) x 775mm (H) x 450mm (D)